



TOUGHmatSM



sustainable entryway matting solution

Looking for a solution for heavy track-in places? **ToughMatSM** is your workhorse. It's a strong, dual purpose mat that scrapes off soil that clings and wipes moisture from footwear on the way in. **ToughMat** provides hard wearing construction that is ideal for all weather conditions.

ToughMat is an affordable, heavy-duty matting solutions for secondary entryways or additional access points in commercial facilities such as hotels, seasonal getaway resorts, schools, office buildings, Class A high rise buildings, retail stores, shopping malls, hospitals, medical buildings and other facilities.



SPECIFICATIONS

Yarn Ply	2400/2 Nylon and 3000/10 Olefin
Yarn Content	73 % Nylon, 27% Olefin
Gauge	5/32
Pile Height	7/32" - 5.54 mm
Color Fastness	Solution Dyed
Stitched Per inch	8.42
Density	4294

Yarn Grade	1
Yarn Weight	Tufted 26 ounces per square yard
Primary Backing	FLW (Fiber lock Woven)
Secondary Backing	Vinyl
Total Weight	91.2 Oz
Total Height	3/8" - 9.52 mm
Sizes Available Stock	2'x3', 3'x5', 4'x6', 6'x10' - Custom sizes available
Wear Warranty	1 Year Limited



ToughMat is designed for use in heavy foot traffic areas. The combination coarse and fine fiber surface is equally effective against foot-tracked particulates and moisture.

ToughMat inhibits fungal growth and is resistant to most common contaminants found in commercial environments including:

Water, Salt Water, Chlorinated Water, Tri-Sodium Phosphate, 5% Detergent Solution, Peanut Oil, Cooking Oil, 24% Sulfuric Acid, 10% Hydrochloric Acid, Ethyl Alcohol, Sodium Hydroxide, Hexane, Mineral Spirits, Gasoline, Diesel Fuel, Motor Oil, Transmission Fluid, 25% Asceic Acid, Brake Fluid.

All our products are made in the U.S.

EcoPath™, ToughMat™ and BrushMat™ are products of Engineered Conversion Systems. 2010/v.1



TO SPEAK WITH AN ECS REPRESENTATIVE, CALL 888-845-9276 | WWW.TOUGHMAT.COM